SA9421

High-Throughput Multi-Gigabit Gateway with 4 x 2.5GbE (1 x PoE+) Ports

Overview

Senao SA9421 high-throughput gateway provides a high-performance network engine with Quad-Core 2.2 GHz processing, 2.5GbE ports, acceleration, and stateful packet inspection capabilities.



Features & Benefits

- Intel® Denverton Quad-core 2.2 GHz processor for intensive packet processing
- Dual 2.5GbE WAN and Dual 2.5GbE ports for line-rate switching
- Dedicated hardware-accelerated encryption engine for IPsec/SSL tunnels
- Physical dual-WAN load balancing and redundant cellular failover safeguards
- 2.5GbE 30W PoE+ physical power output to drive Wi-Fi 6E APs or IP hardware
- Stateful packet inspection firewall with high-efficiency filtering
- Multiple passthrough and physical routing options

Technical Specifications

General

CPU Processor
Quad Core (Intel® Denverton)

Operating Frequency
2.2 GHz

Memory
4 GB (DDR4)

Flash Storage
8 GB

RJ-45 Interface
4 x 2.5GbE

PoE ports
1

PoE Standard
802.3 af/at

Total PoE Budget
30W

I/O Interfaces
1 x RJ-45 console/1 x USB 3.0 Type A

Mounting Method
Wall mount

Security
TPM2.0

Environmental & Physical

Power
54V/1.2A

Operation Temperature
0–40°C

Humidity (non-condensing)
10–95% RH, non-condensing

Dimensions & Weight

Device Dimensions & Weights
Weight: 2.31 lb (1.05 kg)
Length: 8.27 in (210 mm)
Width: 7.07 in (179.5 mm)
Height: 1.38 in (35 mm)

Package Contents
Power adapter
Power cord
RJ-45 Console Cable
Wall Mount Kit
Product Card

Compliance

Regulatory Compliance
FCC Part 15 (Class B)
IC
CE EMC
CB
UL

Hardware Overview



Senao Networks

Product specifications, configurations, certifications, and availability are subject to change without notice and may vary by region and customer program. Final commitments are governed by the applicable quotation, statement of work, or executed agreement.